



HMI and Panels PC

Industrial

Food and Beverage

info@monitor-industriali.com



Caratteristiche

PHX05FA3

Multi-function

PHX08FA3

Cost-effective

PHI10AX3

High Brightness

PHX12AX3

Wide temperature

PHX15AX3

Wide temperature

Caratteristiche	PHX05FA3	PHX08FA3	PHI10AX3	PHX12AX3	PHX15AX3
CPU	Available products with the following processors : ATOM N270, 1.6 GHz, Intel® Celeron® M 1GHZ/600 MHz, AMD LX800 500 MHz, VIA V4 1GHZ/500 MHz, VIA C7 1.5 GHz				
Memory	Max. 1 GB DDR SODIMM	Max. 1 GB DDR SODIMM	Max. 1 GB DDR SODIMM	Max. 1 GB DDR SODIMM	Max. 1 Go DDR SODIMM
Display	5.7" TFT VGA	8.4" TFT SVGA	10.4" TFT SVGA	12" TFT SVGA	15" TFT XGA
Luminance (cd/m²)	400	220	600/230	450	450/260
I/O Connectors	RS-232 x 1 RS-232/422/485 x 1 LAN x 1 USB 2.0 host x 2 Line-out x 1	RS-232 x 2 RS-232/422/485 x 1 LAN x 2 USB 2.0 host x 2 VGA x 1 PS/2 x 1 Line-out x 1	RS-232 x 2 RS-232/422/485 x 1 LAN x 1 USB 2.0 host x 2 VGA x 1 PS/2 x 1 Line-out x 1	RS-232 x 2 RS-232/422/485 x 1 LAN x 2 USB 2.0 host x 2 VGA x 1 PS/2 x 1 Line-out x 1	RS-232 x 2 RS-232/422/485 x 1 LAN x 2 USB 2.0 host x 2 VGA x 1 PS/2 x 1 Line-out x 1
Storage Device	CompactFlash™ card	CompactFlash™ card or HD 2.5"	CompactFlash™ card or HD 2.5"	CompactFlash™ card or HD 2.5"	CompactFlash™ card or HD 2.5"
Bus Expansion	Mini PCI; PC/104	Mini PCI; PC/104	Mini PCI	Mini PCI	Mini PCI
Touchscreen	5 wires Resistive	5 wires Resistive	5 wires Resistive	5 wires Resistive	5 wires Resistive
Operating system	Windows® XP Windows® CE.NET, XPE	Windows® 2000/XP Windows® CE.NET, XPE	Windows® 2000/XP Windows® CE.NET, XPE	Windows® 2000/XP Windows® CE.NET, XPE, Linux	Windows® 2000/XP Windows® CE.NET, XPE, Linux
Dimensions (W x D x H)	209 x 60 x 168 mm (8.21" x 2.34" x 6.59")	280 x 69.3 x 200 mm (11.02" x 2.73" x 7.87")	290 x 72.9 x 248 mm (11.4" x 2.83" x 9.8")	332 x 69.5 x 267 mm (13" x 2.7" x 10.5")	396 x 64.9 x 312 mm (15.6" x 2.5" x 12.3")
Weight	2 kg (4.4 lb)	3.5 kg (7.7 lb)	4.1 kg (9.1 lb)	5.4 kg (12 lb)	6.5 kg (15 lb)
Operating temperature	0°C - 45°C	0°C - 50°C	0°C - 50°C	-20°C - 55°C / 0°C - 50°C	-20°C - 55°C / 0°C - 50°C
Certification	CE	CE	CE	CE	CE
Note	Option : PROFIBUS / bus CAN / CANopen / MPI / ...				
	IP65 (Front)	IP65 (Front)	IP65 (Front)	IP65 (Front)	IP65 (Front)

Food and Beverage HMI and Panels PC



Caratteristiche

PNI10AX3

Panel mount

PNX12AX3

Panel mount

PNX15AX3

Panel mount

TSI15AX3

VESA mount - IP65 Total

TSI17AX3

VESA mount - IP65 Total

CPU	Produits disponibles avec les processeurs suivants :				
	ATOM N270, 1.6 GHz, Intel® Celeron® M 1GHz/600 MHz, AMD LX800 500 MHz, VIA V4 1GHz/500 MHz, VIA C7 1.5 GHz				
Memory	Max. 1 Go DDR SODIMM	Max. 1 Go DDR SODIMM	Max. 1 Go DDR SODIMM	Max. 1 Go DDR SODIMM	Max. 1 Go DDR SODIMM
Display	10.4" TFT SVGA	12" TFT SVGA	15" TFT XGA	15" TFT XGA	17" TFT XGA
Luminance (cd/m²)	600 / 230	450	450 / 260	450 / 260	450 / 260
I/O Connectors	RS-232 x 2 RS-232/422/485 x 1 LAN x 1 USB 2.0 host x 2 VGA x 1 PS/2 x 1 Line-out x 1	RS-232 x 2 RS-232/422/485 x 1 LAN x 2 USB 2.0 host x 2 VGA x 1 PS/2 x 1 Line-out x 1	RS-232 x 2 RS-232/422/485 x 1 LAN x 2 USB 2.0 host x 2 VGA x 1 PS/2 x 1 Line-out x 1	RS-232 x 2 RS-232/422/485 x 1 LAN x 2 USB 2.0 host x 2 VGA x 1 PS/2 x 1 Line-out x 1	RS-232 x 2 RS-232/422/485 x 1 LAN x 2 USB 2.0 host x 2 VGA x 1 PS/2 x 1 Line-out x 1
Storage Device	CompactFlash™ card	CompactFlash™ card or HD 2.5"	CompactFlash™ card or HD 2.5"	CompactFlash™ card or HD 2.5"	CompactFlash™ card or HD 2.5"
Bus Expansion	Mini PCI	Mini PCI	Mini PCI	Mini PCI	Mini PCI
Touchscreen	5 fils Résistive	5 fils Résistive	5 fils Résistive	5 fils Résistive	5 fils Résistive
Operating system	Windows® 2000/XP Windows® CE.NET, XPE	Windows® 2000/XP Windows® CE.NET, XPE, Linux	Windows® 2000/XP Windows® CE.NET, XPE, Linux	Windows® 2000/XP Windows® CE.NET, XPE, Linux	Windows® 2000/XP Windows® CE.NET, XPE, Linux
Dimensions (W x D x H)	290 x 72.9 x 248 mm (11.4" x 2.83" x 9.8")	332 x 69.5 x 267 mm (13" x 2.7" x 10.5")	396 x 64.9 x 312 mm (15.6" x 2.5" x 12.3")	400 x 90 x 324 mm (15.7" x 3.5" x 12.8")	432 x 90 x 324 mm (17.0" x 2.5" x 12.3")
Weight	4.1 kg (9.1 lb)	5.4 kg (12 lb)	6.5 kg (15 lb)	6.5 kg (15 lb)	6.5 kg (15 lb)
Operating temperature	0°C - 50°C	-20°C - 55°C / 0°C - 50°C	-20°C - 55°C / 0°C - 50°C	-20°C - 55°C / 0°C - 50°C	-20°C - 55°C / 0°C - 50°C
Certification	CE	CE	CE	CE	CE
Note	En option : PROFIBUS / busCAN / CANopen / MPI / ...				
	IP65 (Front)	IP65 (Front)	IP65 (Front)	IP65 (Total)	IP65 (Total)

France Switzerland

Monaco

Italia



Z.I. Nord Torre Sapienza - 06055 MARSCIANO (PG)

Tel. 075 885 1026 - 885 2484

Fax 075 885 1170- info@monitor-industriali.com